



D2986-1 RUBBER SPACER

RELEASED
09.01.08

- NOTES:**
- 1) MATERIAL: BLACK NEOPRENE/EPDM/SBR BLEND SHEET (ROLL), 0.125 THICK, PER ASTM D 1056 GRADE 2A1 OR SAE J-18 GRADE 2A1 (REF. DART SPEC. M-4111N-S.125)
 - 2) FINISH: NONE
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: N/A
 - 6) IDENTIFICATION: N/A
 - 7) WEIGHT: 0.3 lbs
 - 8) TOOLING: CUT PER TEMPLATE DT3187-1T1

B	REDRAWN TO CURRENT STANDARDS; TRANSFERRED TO B-SIZE FORMAT; ADDED PART DWG DETAIL; REVISED NOTE 1; REMOVED SUPPLIER AND SPEC DWG NOTES. REASON: ECN#08-589.	MB	08.12.18
A	NEW ISSUE	DS	00.09.26
REV.	DESCRIPTION	BY	DATE
DESIGN		DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN			
CHECKED		DRAWING NO.	REV. B
MFG. APPR.		D2986	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		RUBBER SPACER	NTS
DATE	08.12.18	COPYRIGHT © 2000 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	